

CLAIMS

1

2 1. A fishing lure comprising:

- 3 a. an elongated primary shaft having a first end and a second end;
- 4 b. an elongated lure shaft having a lure shaft first end and a lure shaft second
- 5 end;
- 6 c. the lure shaft at the lure shaft second end fixedly interconnected by shaft
- 7 interconnection means to the primary shaft proximal the second end;
- 8 d. a fish hook means having a hook shaft; the hook shaft secured by hook
- 9 shaft affixing means to the primary shaft proximal the second end;
- 10 e. lure shaft locking means proximal the first end to secure the lure shaft first
- 11 end; means proximal the first end to receive fishing leader.

12

13 2. The fishing lure according to claim 1 further comprising:

- 14 a. the elongated primary shaft and the lure shaft are composed of a rigid
- 15 material;
- 16 b. the shaft interconnection means is by welding, wire wrap, wire twist, or
- 17 ferrule;
- 18 c. hook shaft affixing means to the primary shaft is by welding, wire wrap,
- 19 wire twist or ferrule;
- 20 d. lure shaft locking means is by ferrule means.

21

22 3. The fishing lure according to claim 2 further comprising:

- 23 a. the rigid material composing the primary shaft and the lure shaft formed
- 24 from metal wire;
- 25 b. the shaft interconnection means is by wire twist of the lure shaft proximal
- 26 the lure shaft second end about the primary shaft proximal the second end;
- 27 c. the lure shaft locking means is by a double barrel ferrule; the double barrel
- 28 ferrule having a first barrel receiving and securing the primary shaft proximal the first
- 29 end and having a second barrel receiving the lure shaft at the lure shaft first end;
- 30 d. the hook shaft affixing means to the primary shaft is by a ferrule having a
- first ferrule end and a second ferrule end; the first ferrule end receiving the primary

- 1 shaft at the second end; the second ferrule end receiving the hook shaft; crimping
2 means to secure the ferrule to the primary shaft and to the hook shaft..
3
4 4. The fishing lure according to claim 3, further comprising:
5 a. the metal wire is a copper or tobacco colored wire;
6 b. the lure shaft having a spring function urging the sure shaft away from the
7 primary shaft.
8
9 5. The fishing lure according to claim 4, further comprising:
10 a. at least one bead received by the primary shaft intermediate the double
11 barreled ferrule and the first end;
12 b. one or more spinners received by the primary shaft intermediate the at
13 least one bead and the first end.
14
15
16

17 CERTIFICATE OF EXPRESS MAILING - C.F.R. 1.10
"Express Mail" mailing label number: ET437203475US.
18 Date of Deposit: September 3, 2003.

19 I hereby certify that this paper or fee is
being deposited with the United States
20 Postal Service "Express Mail Post Office to
Addressee" service under 37 CFR 1.10 on the
21 date indicated above and is addressed to
the Commissioner for Patents, P.O. Box 1450,
22 Alexandria, VA 22313-1450.

23 Gina Swift
24 (Printed Name)

25 _____
(Signature)

26
27
28
29
30